VIBRATION CONTROL

TEAM-D

HONGKONG TIANDI INTERNATIONAL TRADING CO.,LTD
香港天弟國際貿易有限公司
ADD：FLAT E2, 6/F. BLOCK E, TSING YI IND CENTER PHASE Ⅱ 1-33 CHEUNG TAT ROAD, TSING YI. NT. HONGKONG ）
地址：香港青衣長達路1-33號青衣工業中心二期E座6樓E2室
HONGKONG TIANDI INTERNATIONAL TRADING MACAU CO.,LTD
香港天弟國際貿易澳門有限公司
ADD：BLOCK G, 14/F. AVENIDA DA PRAIA GRANDE. NO.762-804, CHINA PLAZA, MACAU. ）
地址：澳門南灣大馬路762-804號中華廣場14樓G座
TEL：(852)2320 5957, FAX:(852)2429 8589
WEB: WWW.GZTD888.COM
MAIL: SALES@GZTD888.COM, SALES4@GZTD888.COM

TEAM-D

TEAM-D STRATEGY

- EACH MODEL HAS ITS PATENT AS WELL AS PRATICAL PATENT; ALWAYS HAVE THEIR OWN INTELLECTUAL PROPERTY RIGHTS.
- GLOBAL REGISTRATION
- ESTABLISHMENT OF SALES NETWORK OF SIMKO PRODUCTS AROUND THE WORLD
- INDUSTRIAL-CLASS QUALITY BUT DIY PRICE, APPLICABLE TO ALL COSUMERS

TEAM-D

PROFESSIONAL

DEMOLITION HAMMER ROTARY HAMMER

INDUSTRIAL-CLASS, HEAVY-DUTY

WWW.GZTD888.COM

Warmestly welcome far-sighted business persons around the word to join in an ever lasting partnership of TEAM-D.in providing the best pruducts and the most satisfactory services to our customers.

TEAM-D

Rotary Hammer

SR450-30PA

- Detachable chuck
- Three mode settings - rotary drilling & hammer & Drilling only with idle position
- Chiseling angle adjustable
- Anti-Vibration System
- Speed switch
- Safety clutch device
- 360°Auxiliary handle
- 1050W powerful motor

Rotary Hammer

8 8018 013 SR580-32PA

- SDS-PLUS System
- Capacity: Drill Bit: 32 mm (1-1/4") / Core Bit: 90 mm (3-1/2")
- Two mode settings - rotary drilling & hammer only with idle position
- Chiseling angle adjustable by 12-steps lock
- Anti-Vibration System
- Trigger switch and Ergonomic handle with soft grip
- Variable speed by dial with 6-steps and Constant Speed Control
- Indicator of power supply; Indicator of Carbon Brush maintenance
- Low vibration & noise design with high impact energy
- 360°Auxiliary handle
- Safety clutch device
- 1100W powerful motor

Rotary Hammer

8 8018 014 SR610-35MA

- SDS-MAX System
- Capacity: Drill Bit: 35 mm (1-2/5") / Core Bit: 90 mm (3-1/2")
- Two mode settings - rotary drilling & hammer only with idle position
- Chiseling angle adjustable by 12-steps lock
- Anti-Vibration System
- Trigger switch and Ergonomic handle with soft grip
- Variable speed by dial with 6-steps and Constant Speed Control
- Indicator of power supply; Indicator of Carbon Brush maintenance
- Low vibration & noise design with high impact energy
- 360°Auxiliary handle
- Safety clutch device
- 1100W powerful motor

Rotary Hammer

8 8018 021 SR660-42MA

- SDS-MAX System
- Capacity: Drill Bit: 42 mm (1-2/5") / Core Bit: 110mm (3-1/2")
- Two mode settings - rotary drilling & hammer only with idle position
- Chiseling angle adjustable by 12-steps lock
- Anti-Vibration System
- Trigger switch and Ergonomic handle with soft grip
- Variable speed by dial with 6-steps and Constant Speed Control
- Indicator of power supply; Indicator of Carbon Brush maintenance
- Low vibration & noise design with high impact energy
- 360°Auxiliary handle
- Safety clutch device
- 1200W powerful motor

Specifications	SR450-30PA	SR580-32PA	SR610-35MA	SR660-42MA
Rated Input Power	1050W ■120V/60Hz 8.7A	1100W ■120V/60Hz 10A	1100W ■120V/60Hz 10A	1200W ■120V/60Hz 11.5A
Rated Voltage	220/230/240V~	220/230/240V~	220/230/240V~	220/230/240V~
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
No load speed	0-850min^{-1}	300-760min^{-1}	300-760min^{-1}	235-514min^{-1}
Overall negative beat times	1900-4800min^{-1}	1900-4800min^{-1}	1950-4860min^{-1}	1350-2850min^{-1}
Overall Length	414mm(16-1/5") /5.6Kg(12lbs)	414mm(16-1/5") /5.6Kg(12lbs)	456mm(17-9/10") /5.8Kg(12lbs)	486mm(19-1/10") /6.6Kg(14.5lbs)
Joule	1-6J ■ 1-4.5 ft.lbs	1-6J ■ 1-4.5 ft.lbs	1-7J ■ 1-5 ft.lbs	2-10J ■ 2-8 ft.lbs
Packaging Information				
Case Qty	3pcs	2pcs	2pcs	1pcs
G.W/N.W	20/13.5kgs	17/6.1kgs	18.04/6.44kgs	10.5/6.8kgs
Packing Size(Bmc case)	46x40x38cm	46x26.5x38cm	49.5x27x39cm	59.5x15.7x43cm
PCS/Container(20')	1170pcs	1280pcs	1110pcs	720pcs

TEAM-D

Rotary Hammer

8 8018 018 SR890-52MA

- SDS-MAX System
- Capacity: Drill Bit: 52 mm (1-1/25") / Core Bit:160mm (6-7/25")
- Two mode settings - rotary drilling & hammer only with idle position
- Chiseling angle adjustable by 12-steps lock
- Anti-Vibration System
- Trigger switch and Ergonomic handle with soft grip
- Variable speed by dial with 6-steps and Constant Speed Control
- Indicator of power supply; Indicator of Carbon Brush maintenance
- Low vibration & noise design with high impact energy
- 360°Auxiliary handle
- Safety clutch device
- 1500W powerful motor
- Hammer lock function

Demolition Hammer

8 8016 029 SH520-17HA

- 17mm Hex Shank
- Anti-Vibration System
- lock-on switch and Ergonomic handle with soft grip
- Low vibration & noise design with high impact energy
- 360°Auxiliary handle
- Indicator of power supply
- Chiseling angle adjustable by 6-steps lock

Demolition Hammer

8 8016 028 SH570-18MA

- SDS-MAX System
- Anti-Vibration System
- lock-on switch and Ergonomic handle with soft grip
- Low vibration & noise design with high impact energy
- 360°Auxiliary handle
- Indicator of power supply
- Chiseling angle adjustable by 12-steps lock

Specifications	SR890-52MA	SH520-17HA	SH570-18MA
Rated Input Power	1500W ■120V/60Hz 14A	1200W ■120V/60Hz 11A	1200W ■120V/60Hz 11A
Rated Voltage	220/230/240V~	220/230/240V~	220/230/240V~
Frequency	50/60Hz	50/60Hz	50/60Hz
No load speed	150-305min^{-1}	-	-
Overall negative beat times	1380-2760min^{-1}	3100min^{-1} ■ 3100BPM	3100min^{-1} ■ 3100BPM
Overall Length	560mm(22") /8.9Kg(19.6lbs)	464mm(18-3/10") /5.28Kg(11.6lbs)	489mm(19-1/4") /5.55Kg(12lbs)
Joule	2-15J ■ 1.5-11 ft.lbs	14J ■ 10 ft.lbs	14J ■ 10 ft.lbs
Packaging Information			
Case Qty	1pc	2pcs	2pcs
G.W/N.W	13.8/9.38kgs	20/10.5kgs	20/10.5kgs
Packing Size(Bmc case)	59.5x15.7x43cm	55.5x32x38cm	55.5x32x38cm
PCS/Container(20')	720pcs	900pcs	900pcs

TEAM-D

Demolition Hammer

8 8016 013 SH1100-18MA

- SDS max system
- Chiselling angle adjustable by Variable Lock in 12-step
- 360° Auxiliary handle
- Constant electronics
- Variable speed by dial with 6-step and Constant speed Control
- Lock-on switch
- Anti-Vibration System

Demolition Hammer

8 8011 028 SH1560-30HA

- 30mm(1-1/4")Hex Shank
- 360° Side handle
- Mechanical switch
- Ergonomic side handle soft grip
- Anti-Vibration System,Ergonomic anti- vibration Main handle
- Metal housing and gear box for higher performance and reliability

Demolition Hammer

8 8011 029 SH1770-28HA

- 28mm(1-1/8")Hex Shank
- 360° Side handle
- Mechanical switch
- Ergonomic side handle soft grip
- Anti-Vibration System,Ergonomic anti- vibration Main handle
- Metal housing and gear box for higher performance and reliability

Specifications	SH1100-18MA	SH1560-30HA	SH1770-28HA
Rated Input Power	1500W ■120V/60Hz 12.5A	1500W ■120V/60Hz 15A	1500W ■120V/60Hz 15A
Rated Voltage	220/230/240V~	220/230/240V~	220/230/240V~
Frequency	50/60Hz	50/60Hz	50/60Hz
Overall negative beat times	1000-1900min^{-1} ■ 1000-1900BPM	1400min^{-1} ■ 1400BPM	1400min^{-1} ■ 1400BPM
Overall Length	590mm(23-1/4") /10.5Kg(23lbs)	750mm(29-3/5") /15.6Kg(34lbs)	750mm(29-3/5") /17.7Kg(39lbs)
Joule	6-25J ■ 4-18 ft.lbs	50J ■ 36 ft.lbs	50J ■ 36 ft.lbs
Packaging Information			
Case Qty	1pc	1pc	1pc
G.W/N.W	17/11kgs	24/15.6kgs	25/17kgs
Packing Size(Bmc case)	64x17x39cm	88x19x35.6cm	88x19x35.6cm
PCS/Container(20')	690pcs	480pcs	480pcs

TEAM-D

Demolition Hammer

8 8011 038 SH1800-28HA

- 28mm(1-1/8")Hex Shank
- 360° Side handle
- Mechanical switch
- Ergonomic side handle soft grip
- Anti-Vibration System,Ergonomic anti- vibration Main handle
- Metal housing and gear box for higher performance and reliability

Demolition Hammer

8 8011 039 SH1700-30HA

- 30mm(1-1/4")Hex Shank
- 360° Side handle
- Mechanical switch.
- Ergonomic side handle soft grip
- Anti-Vibration System,Ergonomic anti- vibration Main handle
- Metal housing and gear box for higher performance and reliability

Demolition Hammer

8 8011 040 SH3200-28HA

- 28mm(1-1/8")Hex Shank
- Anti-Vibration System
- Ergonomic anti- vibration Main handle
- Mechanical switch
- Metal housing and gear box for higher performance and reliability

Specifications	SH1800-28HA	SH1700-30HA	SH3200-28HA
Rated Input Power	1600W ■120V/60Hz 15A	1600W ■120V/60Hz 15A	2200W ■120V/60Hz 15A
Rated Voltage	220/230/240V~	220/230/240V~	220/230/240V~
Frequency	50/60Hz	50/60Hz	50/60Hz
Overall negative beat times	1450min^{-1} ■ 1450BPM	1450min^{-1} ■ 1450BPM	950min^{-1} ■ 950BPM
Overall Length	750mm(29-3/5")/17.7Kg(39lbs)	750mm(29-3/5") /17Kg(37lbs)	815mm(32-1/10") /32Kg(70.5lbs)
Joule	55J ■ 40 ft.lbs	55J ■ 40 ft.lbs	78J ■ 57 ft.lbs
Packaging Information			
Case Qty	1pc	1pc	1pc
G.W/N.W	28/17.7kgs	25.5/17kgs	41.5/34.18kgs
Packing Size(Bmc case)	88x19x35.6cm	88x19x35.6cm	89.5x48.5x18.5cm
PCS/Container(20')	480pcs	480pcs	350pcs